



Touchstone Detacher

A practical choice for any parlor



engineering for
a better world

gea.com

Bottom-line efficiency — simple, push-button operation, compact size, integrated logic, with wide range of milking settings.

Flexible — vacuum or air-powered models available.

Milk let-down delay — helps prevent premature detaching.

Vacuum on delay — delays vacuum during attachment to ensure better vacuum stability.

Soft take-off — gentle removal ensures cow comfort and optimal udder health.

Parallel drop feature — allows the cylinder to release after the milking unit is retracted, resulting in better visibility.

Sanitary C.I.P. design — allows a clean-in-place automated washing.



The full flow Visoflow sensor promotes cleaner, faster milking. The Visoflow is made of radel, the strongest and longest lasting plastic in the industry.

Compact size — easily fits most stall configurations.

High-visibility indicator lights — displays the operating mode and shows when milk flow has stopped (automatic or manual settings).

Membrane switches — reliable low cost operation.

Remote start options — choose from a wide array of remote start switches.

Unique air retraction cylinder — air retraction cylinder is constructed of composite material and utilizes the long-life Teflon retraction rope.

Fully adjustable settings — allows proper settings for 2X or 3X milking. Adjustable for use with small ruminants.

Simple dip-switch setup — easy to set all detacher functions.

Milk sweep settings — evacuates residual milk from unit and milk hose. Cycles backflush valve or sensor during washing for enhanced C.I.P.



Touchstone Detacher — air operated



Touchstone Detacher — vacuum operated

GEA North America

GEA Farm Technologies, Inc.

1880 Country Farm Drive, Naperville, IL 60563

Toll Free: 1.877.WS.DAIRY or 1.877.973.2479

GEA Farm Technologies Canada Inc.

4591 boulevard St-Joseph, Drummondville, QC J2A 0C6

Toll Free: 1.877.WS.DAIRY or 1.877.973.2479

gea.com